

AK030 Controlador PTZ



Description

This camera controller has brand new design, adopting a metallic panel with frosted film for the upper shell and CNC oxidation on the lower shell. It has a robust 4D joystick and a clear, backlit LCD display as well as backlit buttons which can be dimmed for use in dark environments. There is a physical On/Off and PoE is supported. Compatible with VISCA, ONVIF, PELCO, and NDI protocols. Web-GUI available for easy setup and updating.

Key Features

- Supports network and serial control methods.
- Supports VISCA, ONVIF, PELCO-P, PELCO-D and NDI protocols.
- Individual knobs with level indicators for iris, focus, white-balance, pan/tilt speed and zoom speed.
- Velocity sensitive zoom control via joystick twist or dedicated rocker switch.
- Four instant-access buttons for quick camera selection. Control up to 255 cameras and 255 for each camera.
- Support Power over Ethernet. Power supply and control can be conducted through one network cable, making the wiring simpler.
- Security protection: password and Kensington lock protection to prevent illegal operations and settings and protect the security of the device.



**AUDIOVISUALS
YOU CAN TRUST**

Functions and Parameters

Communication Method	Network: RJ45, Serial port: RS422, RS485, RS232
Communication Protocols	Network: ONVIF, IP VISCA, SONY VISCA OVER IP, NDI Serial Port: VISCA, PELCO-D, PELCO-P
Communication Baud Rate	2400bps, 4800bps, 9600bps, 19200bps, 38400bps, 115200bps
Interfaces	5PIN crimping terminal (RS422, RS485), RJ45 (RS232/RS485/RS422), RJ45 (network), 8PIN Phoenix terminal (TALLY), POE
Joystick	4 dimensions
Display	LCD blue screen
Power Supply	DC12V1A±10%
Power Consumption	6W MAX
Working Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 70°C
Humidity	≤90%RH (No frosting)
Dimension	270mm (L) X135mm (W) X110mm(H)
Update Method	WEB update



**AUDIOVISUALS
YOU CAN TRUST**

Dimensions

